



APPLICATION FOR CTF CERTIFIED BOWLING CENTRE CERTIFICATE 20\_\_\_\_\_ TO 20\_\_\_\_\_ SEASON

CENTRE INFORMATION

Date of inspection: \_\_\_\_\_

Certification # \_\_\_\_\_ Name of Centre \_\_\_\_\_

CTFBA # \_\_\_\_\_ Name of CTF Association \_\_\_\_\_

Bowling Centre Mailing Address \_\_\_\_\_

Bowling Centre Street Address \_\_\_\_\_

Name of Manager \_\_\_\_\_ Business Phone # ( ) \_\_\_\_\_

Name of Owner \_\_\_\_\_ Business Phone # ( ) \_\_\_\_\_

Owner Mailing Address \_\_\_\_\_

Lanes in Bowling Centre \_\_\_\_\_ Lanes Have Been Added \_\_\_\_\_ Lanes Have Been Replaced \_\_\_\_\_

Lanes to be Certified are Numbered \_\_\_\_\_ -- \_\_\_\_\_  Initial  Annual Renewal

Class of Bowling Centre  Commercial  Military  Fraternal  University  Other

Automatic Scorers  Yes  No If Yes : Manufactured By \_\_\_\_\_ Series \_\_\_\_\_

Pinsetters  Manual  Semi-automatic  Automatic Manufactured By \_\_\_\_\_ Series \_\_\_\_\_

Pin Decks  Wood  Synthetic If Synthetic Manufactured By \_\_\_\_\_ System \_\_\_\_\_

Lanes  Wood  Synthetic If Synthetic Manufactured By \_\_\_\_\_ System \_\_\_\_\_

Lanes  Wood  Synthetic If Synthetic Manufactured By \_\_\_\_\_ System \_\_\_\_\_

RESURFACER/INSTALLER INFORMATION

Resurfacer Stencil or Synthetic Product ID Code Appears on All Lanes:  Yes  No

Resurfaced/Installed by \_\_\_\_\_ Date \_\_\_\_\_

Address of Resurfacing Firm \_\_\_\_\_

Screened and Recoated Only

Wood Surface Top Coat. . . . .  Urethane  Water Base  Lacquer  Epoxy  100% Solid

Manufactured by \_\_\_\_\_

INSPECTOR INFORMATION – SUBMISSION OF FORM TO CTF NATIONAL OFFICE - We, the undersigned, representing the above listed bowling associations, have measured and inspected the physical specifications of the lanes referred to in this report and certify the measurements listed herein to be accurate.

FORWARD ALL PAGES TO CTF NATIONAL OFFICE

Signature of Inspector \_\_\_\_\_ CLI# \_\_\_\_\_ Bus. Phone # \_\_\_\_\_ Home Phone # \_\_\_\_\_

Signature of Inspector \_\_\_\_\_ CLI# \_\_\_\_\_ Bus. Phone # \_\_\_\_\_ Home Phone # \_\_\_\_\_

Print Name of Inspection Coordinator \_\_\_\_\_ Bus. Phone # \_\_\_\_\_ Home Phone # \_\_\_\_\_

Address of Inspection Coordinator \_\_\_\_\_ Amount Enclosed \$ \_\_\_\_\_

I Hereby Apply for a CTF Bowling Centre Certificate and Acknowledge Receipt of One Copy of this Application.

Signature of Bowling Centre Owner or Authorized Representative \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

I Do Not Want a Copy of this Report Forwarded to my Resurfacer/Installer

Mail Application to CTF National Office, 916 – 3<sup>rd</sup> Avenue North, Lethbridge, AB T1H 0H3



Certification # \_\_\_\_\_ Name of Bowling Centre \_\_\_\_\_ Date \_\_\_\_\_, 20\_\_\_\_ Page 2

**SECTION A**

**THE FOLLOWING MEASUREMENTS MUST BE COMPLETED FOLLOWING INSTALLATION OR REPLACEMENT.**

If replacement occurs, only answer the affected areas.

- 1. **APPROACH LENGTH** – (not including foul line) Specification: Minimum of 15' Do all approaches apply? Yes  No
- 2. **FOUL LINES** – Specification: Minimum 3/8" - Maximum 1" Do all foul lines comply? Yes  No
- 3. **TARGETS AND GUIDES** – (Including Approaches) Are all targets and guides equally & properly spaced? Yes  No
- 4. **LANE LENGTH** – (Foul Line to Centre of #1 Pin Spot) Specification: Minimum 59' 11 1/2" – Max. : 60' 1/2" Do all lanes comply? Yes  No
- 5. **PIN SPOTS**– Specification: Diameter 2 1/4" – 12" Centre to centre Do all pin spots comply? Yes  No
- 6. **KICKBACK PLATES** – (Fibre or synthetic) Specification: Maximum 3/16" thick Do all kickback plates comply? Yes  No

**SECTION B**

**THE FOLLOWING MEASUREMENTS MUST BE COMPLETED FOLLOWING INSTALLATION, REPLACEMENT OR RESURFACING:**

- 7. **PIT DEPTHS** – Specification: Automatic – Minimum 4 3/4" Manual or semi-automatic – Minimum 9 1/2" Do all pit depths comply? Yes  No
- 8. **PIT LENGTHS** – Specification: Automatic – Minimum 25" Manual or semi-automatic.– Minimum 30" Do all pit lengths comply? Yes  No
- 9. (a) **SYNTHETIC OR PANELIZED LANS/PIN DECKS**– Specification: Maximum .050 inch Do gaps between sections comply? Yes  No

**\* SECTION C**

**THE FOLLOWING MEASUREMENTS MUST BE COMPLETED YEARLY, REGARDLESS OF RESURFACING, RECOATING OR NO WORK BEING PERFORMED.**

- 9. (b) **SYNTHETIC OR PANILIZED LANES/PINDECKS** – Specification Maximum .025 inch. Do drops from trailing to leading edge comply? Yes  No
- 10. **APPROACH DEPRESSIONS – (5" FROM FOUL LINE)** Specification: Maximum 1/4" (250/1000) Do all approaches comply? Yes  No
- 11. **AUTOMATIC FOUL DETECTING DEVICES** Are all devices operational? Yes  No
- 12. **GUTTERS** – Do all gutters have square bottoms and slope gradually from a point opposite or within 15" ahead of the #1 Pin Spot? Yes  No
- 13. **PINSPOTTING** – Specification: On spot – first cycle Do all pinsetters comply? Yes  No
- 14. **EDGE STRIPS** – (fibre or synthetic) Specification: Width – Maximum 1/2" Radius – Maximum 5/32" Do all edge strips comply? Yes  No

**NOTE, IF YOU ANSWERED "NO" TO ANY OF THE ABOVE, PLEASE LIST THE ITEM AND THE LANE NUMBER(S) WHERE THE DISCREPANCIES EXIST: FOR EXAMPLE, ITEM #1 – LANES 2, 4, 10**

---



---



---



---



---



---





Certification # \_\_\_\_\_ Name of Bowling Centre \_\_\_\_\_ Date \_\_\_\_\_, 20\_\_\_\_ Page 4

INSTRUCTIONS: CHECK FOR CROSSWISE TILT AND DEPRESSIONS AT EACH TEST POINT INDICATED. COMPLETE ALL BOXES  
SPECIFICATION: MAXIMUM .040 (40/1000)

ITEM	DISTANCE FROM FOUL LINE	REMEMBER TO COMPLETE TILTS & DEPRESSIONS	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #	Lane #		
*22	Measure Between 10-15'	Crosswise Tilts >																	
		Depressions	- 6" to 12" from 10 pin side >																
			- Middle of Bowling Lane >																
	Insert Distance	- 6" to 12" from 7 pin side >																	
*22	Measure Between 30-40"	Crosswise Tilts >																	
		Depressions	- 9" to 15" from 10 pin side >																
			- Middle of Bowling Lane >																
	Insert Distance	- 9" to 15" from 7 pin side >																	
*22	Measure Between 50-55'	Crosswise Tilts >																	
		Depressions	- 12" to 18" from 10 pin side >																
	Insert Distance		- 12" to 18" from 7 pin side >																

REMARKS: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

REMEMBER TO CIRCLE ALL DISCREPANCIES ON PAGES 2, 3 AND 4 BEFORE PROVIDING A COPY TO CENTRE MANAGEMENT